



## Specifications Ledvance LED Downlight Alu DN200 25W 2370lm 100D - 865 Daylight | 215mm - IP44

[View Product](#)

### General Information

|                      |                                |
|----------------------|--------------------------------|
| SKU                  | 233341                         |
| EAN                  | 4058075091535                  |
| Manufacturer Code    | 4058075091535                  |
| Brand                | Ledvance                       |
| Manufacturer Name    | DL ALU DN200 25W/6500K WT IP44 |
| Budgetlight warranty | 5 Years                        |
| Average Lifetime (h) | 50000                          |

### Technical Information

|                             |                |
|-----------------------------|----------------|
| Emergency Lighting          | No             |
| Tiltable                    | No             |
| Technology                  | LED Integrated |
| Replaces (Watt)             | 2x42           |
| Wattage                     | 25W            |
| Voltage (V)                 | 220-240        |
| Dimmable                    | Not Dimmable   |
| Colour Code                 | 865 Daylight   |
| Colour temperature (Kelvin) | 6500 Daylight  |
| Colour Rendering (Ra)       | 80-89          |
| Colour of Light             | White          |

|                         |                                       |
|-------------------------|---------------------------------------|
| Light Colour Options    | Single Color                          |
| Inclusief Driver        | Yes                                   |
| Beam Angle (degree)     | 100                                   |
| Luminous Flux (Lumen)   | 2370lm                                |
| Lumen per watt          | 95                                    |
| Powerfactor             | >0.90                                 |
| Installation Depth (mm) | 120                                   |
| Unified Glare Rating    | < 28 - for hallways and storage rooms |
| Optische Afdekking      | PMMA (Polymethyl methacrylate)        |
| Suitable for Outdoor    | No                                    |
| Type product            | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP44                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Bedrijfstemperatuur    | -20 to +45                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Product Serie          | DOWNLIGHT ALU                 |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 61  |
| Diameter (mm) | 215 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**